

OPTICAL TRANSMITTER

Patent Number: JP6216406
Publication date: 1994-08-05
Inventor(s): MUKAI MIKIO
Applicant(s): SONY CORP
Requested Patent: ☐ JP6216406
Application: JP19930005011
Priority Number(s):
IPC Classification: H01L31/12
EC Classification:
Equivalents:

Abstract

PURPOSE:To detect partial reflection from a light-emitting device efficiently, and to stabilize an optical output by housing a control circuit keeping the optical output approximately constant and a ray converging means into a single package on the basis of the optical output signals of the light-emitting device and a driver circuit and a photo-sensor detecting a part of output rays.

CONSTITUTION:Output rays X from a light-emitting device 1 are formed in pulses driven by a driver circuit, and output to the outside of a package from the outgoing section of the package 28 for a transparent cap. A part of output rays is partially reflected by the package 28 for the cap, and the partially reflected rays are projected to a plurality of convex lenses 32 as rays Y for detection. Irregularly reflected rays in a hollow section 30 are also projected to a plurality of the convex lenses 32 as rays Y for detection, and converged to photo-sensors 18 respectively. Accordingly, even when inspection rays Y composed of partially reflected rays, etc., are weak, optical sensibility in the photo-sensors 18 is improved. Detected optical signals in the photo-sensors 18 are used for controlling the driver circuit of the negatively fed back light-emitting device 12.

Data supplied from the esp@cenet database - I2

06216406 A



(19)

(11) Publication number:

01

Generated Document.

PATENT ABSTRACTS OF JAPAN

(21) Application number: **05005011**(51) Intl. Cl.: **H01L 31/12**(22) Application date: **14.01.93**

(30) Priority:

(43) Date of application
publication: **05.08.94**(84) Designated contracting
states:(71) Applicant: **SONY CORP**(72) Inventor: **MUKAI MIKIO**

(74) Representative:

(54) OPTICAL TRANSMITTER

(57) Abstract:

PURPOSE: To detect partial reflection from a light-emitting device efficiently, and to stabilize an optical output by housing a control circuit keeping the optical output approximately constant and a ray converging means into a single package on the basis of the optical output signals of the light-emitting device and a driver circuit and a photo-sensor detecting a part of output rays.

CONSTITUTION: Output rays X from a light-emitting device 1 are formed in pulses driven by a driver circuit, and output to the outside of a package from the outgoing section of the package 28 for a transparent cap. A part of output rays is partially reflected by the package 28 for the cap, and the partially reflected rays are projected to a plurality of convex lenses 32 as rays Y for detection. Irregularly reflected rays in a hollow

section 30 are also projected to a plurality of the convex lenses 32 as rays Y for detection, and converged to photo-sensors 18 respectively.

Accordingly, even when inspection rays Y composed of partially reflected rays, etc., are weak, optical sensibility in the photo-sensors 18 is improved. Detected optical signals in the photo-sensors 18 are used for controlling the driver circuit of the negatively fed back light-emitting device 12.

COPYRIGHT: (C)1994,JPO&Japio

